



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			STND125L-N			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	MAX. 0.570A	
			DC24V			
			AC110V		MAX. 0.200A	
			AC220V			
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	6~30	±0.1	±0.2	±0.5	±1	H.M.SEO	J.Y.KIM		J.W.KIM	3	2022.12.23	
	30~120	±0.15	±0.3	±0.8	±1.5	TITLE STND125L-N OUTLINE DRAWING 			MODEL STND125L-N			
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4				DWG. NO. STND125L-N_OUT			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

