



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S150UL			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V ~ DC24V	0.08W	MAX. 0.300A	
			AC110V		0.060A	
			AC220V		0.030A	
			VOLUME			MAX. 90dB at 1m
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-		
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20			
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1	TITLE S150UL OUTLINE DRAWING								
	30~120	±0.15	±0.3	±0.8	±1.5								MODEL S150UL	
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4	DWG. NO. S150UL_OUT									
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°										
	10~50	±0°30'	±1°	±2°										
	50~120	±0°20'	±0°30'	±1°										
	120~400	±0°10'	±0°13'	±0°30'	SCALE N/S	SIZE A4			REV 00	SHEET 1/1				

A4(297X210)