


STG40L : DC
STG40LF : DC
STG40L-BZ : DC

STG40LF-BZ : DC



MARK	DATE	REVISION	REVISER	APP. BY
△1				
△2				
△3				

MODEL NO			STG40L/ L-BZ/ STG40LF/ LF-BZ			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			PIPE-AL			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE(), WHITE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	0.075A/LAYER1	
			DC24V		0.045A/LAYER1	
VOLUME			MAX. 85dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65 (BZ TYPE-IP54)			
CABLE ENTRY			ø9.5 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

LAYER	L1	L2
1	334	376
2	364	406
3	394	436
4	424	466
5	454	496

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE STG40L SERIES OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5			MODEL STG40L SERIES					
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4								
	0~10	±1°		±1°30'	±3°			DWG. NO. STG40L SERIES-OUT					
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°			SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	120~400	±0°10'		±0°13'	±0°30'								

Qlight